







COMAP

CAJA 922001 – BASIN TAP PAIR

C	Specification					
		Finish	Ch	Chrome		
		Body	Brass			
	Fittings	Fittings Metal backnut 8		knut & v	vasher	
		Connection	1⁄2"	1/2" BSP threaded t		il
	Min dynamic pressure			0.1		
	Max dynamic pressure			6		
		Max static pressure				16
		Max water temperature			е	60°C
			Flow rates			
- 33 - 80 - 80 - 80 - 80 - 80 - 80 - 80	-	Pressure	0.1	0.5	1	3
		L/min	8	22.5	32.6	57.2
		All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance.				
- 77	Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.					
		Performance details are based on trials under test conditions and for guidance only.				
		The Company reserves the right to change product specification without prior notice.				
Features & Benefits			Certifi	cation	IS	
10 YEARL Low PressureInlet Tail	Flow Straightener	13.8 Tested at 0				
Flow Aerator Single Flow						

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

